



NORMAL OPERATING CONDITION:
 - WORKING PRESSURE
 EXTERNAL: Atmospheric
 INTERNAL: 10^{-1} mbar
 - WORKING TEMPERATURE: 20° - 250° MASS : 4.5 Kg

QUANT.	DESCRIPTION	POS.	MAT.	SENS./S.ASS.	OBSERVATIONS	REF.CERN
1	TENSION SPRING FOR \varnothing 63 -	5				LHCVSR...0239
16	HEX.COUNTERSUNK SCREW M3x6	4	Stainless steel A4 SILVER COATED			BOSSARD BN4.719
1	TRANS. TUBE FLANGE \varnothing 63 L 206	3				LHCVSR...0062
1	RF CONTACT \varnothing 63	2				LHCVSR...0057
1	WARM BELLOWS DN100 L300 WITHOUT PORT	1				LHCVBU...0022

Warm Modules - Body DN100/-20 - Insert 63/63R - No Ports Long		ECHELLE SCALE 1:1	DES/DRA. J. VENTURINI 2004-08-24
			CONTROLLED L. FAISANDEL 2006-07-11
			RELEASED A VIDAL 2006-07-11
			APPROVED - -
			LHCVM...WARM*00000,V04.8,V04.82056PL
			REPLACE/REPLACES
UNDER APPROVAL	FOR INFORMATION	QUAL. A	LHCVMABB0002
			SIZE 1 IND. A

A	2006-07-11	J. VENTURINI		MODIF. T.SPRING LHCVSR...0041 TO LHCVSR...0239
IND.	DATE	NOM/NAME	ZONE	MODIFICATION

DESIGN: RIGIDITE, TOLERANCES SELON NORME ISO
 DRAWING: RUGOSITY, TOLERANCES ACCORDING TO ISO STANDARD
 PROJECTION
 CERN
 ORGANISATION FOR EUROPEAN NUCLEAR RESEARCH
 Ce dessin ne peut être utilisé à des fins commerciales sans autorisation écrite.
 This drawing may not be used for commercial purposes without written authorisation.