



NORMAL OPERATING CONDITION:
 - WORKING PRESSURE
 EXTERNAL: Atmospheric
 INTERNAL: 10^{-1} mbar
 - WORKING TEMPERATURE: 20° - 250° MASS : 7.8Kg

QUANT.	DESCRIPTION	POS.	MAT.	OBSERVATIONS	REF.CERN
1	Tension Spring	5		LHCVSR...0011	
16	HEX.COUNTERSUNK SCREW M3x6	4	stainless steel A4 Silver coated	Bossard BN4 719	
1	RF CONTACT Ø 80	3		LHCVSR...0005	
1	TRANSITION TUBE FLANGE Ø 80/63	2		LHCVSR...0061	
1	LEFT WARM BELLOWS DN100 2 PORTS -	1		LHCVBU...0100	

WARM Modules - Body DN100/-20 - Insert 63/80R - Parts b40/c63 N		ECHELLE SCALE	DES/DRA.	J VENTURINI	2005-12-06
		1:1	CONTROLLED	L FAISANDEL	2005-12-20
			RELEASED	A VIDAL	2005-12-20
			APPROVED		
			LHCV,VM...WARM*00000,V04.8,V04.82*5PL		
			REPLACE/REPLACES		
IND.	DATE	NOM/NAME	ZONE	MODIFICATION	

DESIGN: RIGIDITE, TOLERANCES SELON NORME ISO DRAWING: RIGIDITE, TOLERANCES ACCORDING TO ISO STANDARD
 PROJECTION
 ORGANISATION: EUROPEAN ORGANIZATION FOR NUCLEAR RESEARCH
 Ce dessin ne peut être utilisé à des fins commerciales sans autorisation écrite. This drawing may not be used for commercial purposes without written authorisation.