



NORMAL OPERATING CONDITION:  
 - WORKING PRESSURE  
   EXTERNAL: Atmospheric  
   INTERNAL:  $10^{-10}$  mbar  
 - WORKING TEMPERATURE: 20° - 250°    MASS : 4.8Kg

QUANT.	DESCRIPTION	POS.	MAT.	SENS./S.ASS.	OBSERVATIONS	REF.CERN
1	TENSION SPRING FOR $\varnothing$ 63 -	5			LHCVSR...0239	
16	HEX.COUNTERSUNK SCREW M3x6	4	Stainless steel A4 SILVER COATED		BOSSARD BN4.719	
1	TRANSITION TUBE FLANGE $\varnothing$ 100/6	3			LHCVSR...0055	
1	RF CONTACT $\varnothing$ 63 -	2			LHCVSR...0057	
1	WARM BELLOWS DN100 1PORT FOR ELLIPTIC	1			LHCVBU...0053	

ENS./ASS.	SENS./S.ASS.	ECHELLE SCALE	DES/DRA.	J. VENTURINI	2006-08-31
Warm Modules - Body DN100/.20 - Insert 100/63R - Ports d100			CONTROLLED	L. FAISANDEL	2006-10-26
			RELEASED	A. VIDAL	2006-10-26
			APPROVED		
			LHCV,VM...WARM*00000,V04.8,V04.8230PL REPLACE/REPLACES		

IND.	DATE	NOM/NAME	ZONE	MODIFICATION
A	2006-08-26	J. VENTURINI		UPDATE TENSION SPRING VSR...0041TO 0239

DESIGN: RIGIDITE, TOLERANCES  
 SELON NORME ISO  
 DRAWING: RUGOSITY, TOLERANCES  
 ACCORDING TO ISO STANDARD  
 PROJECTION  
 EUROPEAN ORGANIZATION FOR NUCLEAR RESEARCH  
 CERN  
 Ce dessin ne peut être utilisé à des fins commerciales sans autorisation écrite.  
 This drawing may not be used for commercial purposes without written authorisation.