



NORMAL OPERATING CONDITION:
 _ WORKING PRESSURE
 EXTERNAL: Atmospheric
 INTERNAL: 10⁻¹¹ mbar
 _ WORKING TEMPERATURE: 20° - 250° MASS : 3.6Kg

QUANT	DESCRIPTION	POS	MAT.	OBSERVATIONS	REF.CERN
1	TENSION SPRING Ø 60	5		LHCVSR_0151	
16	HEX.COUNTERSUNK SCREW M3x6	4	Stainless steel A4 SILVER COATED5µ	BOSSARD BN4 719	
1	TRANSITION TUBE FLANGE Ø 60L66	3		LHCVSR_0023	
1	RF CONTACT Ø 60	2		LHCVSR_0024	
1	WARM BELOWS DN100 WITHOUT PORT L 120MM	1		LHCVBU_0036	
	ENS./ASS.		S.ENS/S.ASS.		

Warm Modules - Body DN100/_6 - Insert 60/60R - No ports long		ECHELLE SCALE 1:1	DES/DRA. J VENTURINI 2005-12-13
WARM MODULE TYPE VMDQB		CONTROLLED L FAISANDEL 2005-12-20	RELEASED A VIDAL 2005-12-20
		APPROVED - -	LHCVM...WARMMOD000,V04-8,V04-82170PL
REPLACE/REPLACES			
RELEASED BY PROJECT ENGINEER	FOR INFORMATION	GAC -	LHCVMDQB0001
IND. 2	SIZE 2	IND. 2	

DESSIN, RUGOSITE, TOLERANCES SELON NORME ISO
 DRAWING, RUGOSITY, TOLERANCES ACCORDING TO ISO STANDARD
 PROJECTION
 ORGANISATION EUROPEENNE POUR LA RECHERCHE NUCLEAIRE
 EUROPEAN ORGANIZATION FOR NUCLEAR RESEARCH
 CERN
 Ce dessin ne peut être utilisé à des fins commerciales sans autorisation écrite.
 This drawing may not be used for commercial purposes without written authorisation.

IND.	DATE	NOM/NAME	ZONE	MODIFICATION