



NORMAL OPERATING CONDITION:
 _ WORKING PRESSURE
 EXTERNAL: Atmospheric
 INTERNAL: 10⁻¹¹ mbar
 _ WORKING TEMPERATURE: 20° - 250° MASS : 3.7Kg

1	TENSION SPRING FOR Ø 57 -	5		LHCVSR__0157	
16	HEX.COUNTERSUNK SCREW M3x6	4	Stainless steel A4 SILVER COATED	BOSSARD BN4 719	
1	TRANSITION TUBE FLANGE - Ø 57	3		LHCVSR__0156	
1	RF CONTACT Ø 57 L 118.5 -	2		LHCVSR__0141	
1	WARM BELLOWS DN100 - WITHOUT PORT	1		LHCVBU__0012	
QUANT	DESCRIPTION	POS	MAT.	OBSERVATIONS	REF.CERN
	ENS./ASS.		S.ENS/S.ASS.		

Warm Modules - Body DN100/_20 - Insert 57/57R - No ports		ECHELLE SCALE 1:1	DES/DRA. J VENTURINI 2006-02-02
WARM MODULE TYPE VMAPA		CONTROLLED L FAISANDEL 2006-02-03	RELEASED A VIDAL 2006-02-03
		APPROVED - -	
		LHCVM...WARM0000,V04-8,V04-82180PL	REPLACE/REPLACES
RELEASED BY PROJECT ENGINEER	FOR INFORMATION	GAC -	SIZE IND. LHCVMAPA0001 2

ORGANISATION EUROPEENNE POUR LA RECHERCHE NUCLEAIRE
 EUROPEAN ORGANIZATION FOR NUCLEAR RESEARCH
 CERN
 DESSIN, RUGOSITE, TOLERANCES SELON NORME ISO
 DRAWING, RUGOSITY, TOLERANCES ACCORDING TO ISO STANDARD
 PROJECTION
 Ce dessin ne peut être utilisé à des fins commerciales sans autorisation écrite.
 This drawing may not be used for commercial purposes without written authorisation.

IND.	DATE	NOM/NAME	ZONE	MODIFICATION
------	------	----------	------	--------------